

T8 Single Opalescent Mask Battens


T8單支乳白罩防水支架

Series Type: IPB-TM-N-S

Features 產品特點 >>

- The lampshade and lamp body are made of high-quality plastics, which have anti-UV and flame-retardant properties and high mechanical strength
- There are protective coils and waterproof joints at both ends of the lamp body, with good sealing performance and protection level Ip65
- Reasonable light distribution design, soft light, effectively suppress glare, and effectively protect eyesight
- Installation method: Ceiling type, fixed by hanging wire and line pipe hook
- Scope of application: factories, flyovers, basements, parking lots, food courts and other environments

- 灯罩、灯体由优质塑料制造, 具有防UV和阻燃特性, 机械强度高
- 灯体两端有护线圈和防水接头, 密封性能好, 防护等级IP65
- 合理配光设计, 光线柔和, 有效抑制眩光, 有效的保护视力
- 安装方式: 吸顶式、采用吊线、线管吊钩固定
- 适用范围: 工厂、天桥、地下室、停车场、食品场等环境



(Unit : mm)

Specification 產品規格 >>

Model 型號	Size 尺寸 (mm)	Number Of Tube 燈管數量 (pcs)	Material 材料	IP Grade IP等級	Carton Size 外箱尺寸 (mm)	PCS / CTN 每箱數量 (pcs)
IPB-TM0608-N-S	663*86*90	1pcs*0.6m(2ft)	ABS+PC	IP 65	695*285*220	9
IPB-TM1208-N-S	1265*86*90	1pcs*1.2m(4ft)	ABS+PC	IP 65	1295*285*220	9
IPB-TM1508-N-S	1570*86*90	1pcs*1.5m(5ft)	ABS+PC	IP 65	1595*290*300	9

- The product is a separate bracket, which can be equipped with LED tube as required
- Lamp light effect (lm/W), power (W), color rendering index (CRI), length, can be customized according to customer needs

- 產品為单独支架, 可按需求配備LED燈管
- 燈管光效 (lm/W)、功率 (W)、顯色指數 (CRI)、長度, 可根據客戶需求定制

T8 Double Opalescent Mask Battens


T8雙隻乳白罩防水支架

Series Type: IPB-TM-N-D

Features 產品特點 >>

- The lamp body design has the functions of dustproof, moisture-proof and waterproof
- Good toughness and strong impact resistance
- With high transmittance and even luminance
- With high thermal conductivity and good heat dissipation
- High elastic rubber ring seal between lamp body and mask, stainless steel clasp,

- 燈體設計具有防塵, 防潮, 防水功能
- 韌性好, 抗衝擊性強
- 透光率高, 亮度均勻
- 導熱係數高, 散熱好
- 燈體與面罩之間採用高彈性橡膠圈密封, 不銹鋼表扣



(Unit : mm)

Specification 產品規格 >>

Model 型號	Size 尺寸 (mm)	Number Of Tube 燈管數量 (pcs)	Material 材料	IP Grade IP等級	Carton Size 外箱尺寸 (mm)	PCS / CTN 每箱數量 (pcs)
IPB-TM0608-N-D	660*86*77	2pcs*0.6m(2ft)	PC+PC	IP 65	630*280*255	9
IPB-TM1208-N-D	1200*86*77	2pcs*1.2m(4ft)	PC+PC	IP 65	1230*280*255	9
IPB-TM1508-N-D	1500*86*77	2pcs*1.5m(5ft)	PC+PC	IP 65	1530*280*255	9

- The product is a separate bracket, which can be equipped with LED tube as required
- Lamp light effect (lm/W), power (W), color rendering index (CRI), length, can be customized according to customer needs

- 產品為单独支架, 可按需求配備LED燈管
- 燈管光效 (lm/W)、功率 (W)、顯色指數 (CRI)、長度, 可根據客戶需求定制