

# LED T5 DC Tube & 0-10V LED Dimming Driver




**Model :LT-R506 / LT-R512/LT-R515 + DC-LT12-DIM-010**

1. Uniform light emission
2. High luminous output (100-150lm/w) & lower power consumption
3. SPM Design - Power circuit protection to cut off individual LEDs when mal-function
4. T6 tube body to achieve the best light effect
5. Control mode: 0-10V
6. Dimming range from 0-100 %
7. Compliant with safety extra low voltage standard.
8. THD < 15%
9. Flicker Free



Model:LT-R506 / LT-R512 / LT-R515



Model:DC-LT12-DIM-010

## Standard

Tube Dimension	∅ 20mm*548/1148/1448mm
Voltage (V)	DC30~42V
Lamp Holder	G5
Beam Angle	180 degree
CRI	>80Ra
Luminous Efficacy	100-150 lm/w
Power Factor	> 0.90
THD	< 15%

Power (W)	Model:	8W / 100lm/W / Total 800lm
	LT-R506	8W / 120lm/W / Total 960lm
		8W / 140lm/W / Total 1120lm
Power (W)	Model:	8W / 150lm/W / Total 1200lm
	LT-R512	16W / 100lm/W / Total 1600lm
		16W / 120lm/W / Total 1920lm
		16W / 140lm/W / Total 2240lm
Power (W)	Model:	16W / 150lm/W / Total 2400lm
	LT-R515	20W / 100lm/W / Total 2000lm
		20W / 120lm/W / Total 2400lm
		20W / 140lm/W / Total 2800lm
		20W / 150lm/W / Total 3000lm

Cover Material	Aluminium , PC Cover
Color Temperature	2700K/3000K/4000K/6000K
Life Time	50,000(H)

