


## **T8 Single Dustproof Battens**

T8單隻防尘支架

Series Type: DBA-S-N

#### Features 產品特點 >>

- The shell adopts arc surface streamline design, beautiful appearance, novel and unique;
- Using high-quality cold-rolled steel plate, electrostatic spraying treatment, durable;
- The lamp holder adopts a cut-in and rotating design, with tight contact, safe and reliable;
- Applicable places: homes, schools, offices, conference rooms, factories, etc.
- Installation mode: ceiling installation or suspension installation
- 外殼採用弧面流線設計,造型美觀,新穎獨特
- 採用優質冷軋鋼板,靜電噴塗處理,經久耐用
- 燈座採用切入旋轉式設計,緊緩型接觸,安全可靠
- 適用場所:家庭、學校、辦公室、會議室、工廠等
- 安裝方式:吸頂安裝或懸掛安裝



## Specification 產品規格 >>

Model 型號	Size 尺寸	Number Of Tube 燈管數量	Material 材料	IP Grade IP等級	Weight 重量	Carton Size 外箱尺寸	PCS / CTN 每箱數量
	(mm)	(pcs)			(kg)	(mm)	(pcs)
DBA-S0609-N	630*95*42	1pcs*0.6m(2ft)	Iron+PC	IP 20	0.4	660*290*210	12
DBA-S1218-N	1230*95*42	1pcs*1.2m(4ft)	Iron+PC	IP 20	0.8	1260*290*210	12

- The product is a separate bracket, which can be equipped with LED tube as required
- Lamp light effect (Im/W), power (W), color rendering index (CRI), length, can be customized according to customer needs
- 產品為单独支架,可按需求配備LED燈管
- 燈管光效 (Im/W)、功率 (W)、顯色指數 (CRI)、長度,可根據客戶需求定制

# **T8 Prism Dustproof Batten**

T8棱鏡防塵支架

Series Type: DBA-FA-T

#### Features 產品特點 >>

- This Batten is suitable for T8 LED tube installation
- The lamp body is made of high-quality cold-rolled steel plate with a thickness of 0.4mm, and the is anti-rust and durable, and is not easy to wear
- With a prismafic diffuser
- Dustand insect-proof
- 此板條適用於T8 LED管安裝
- 燈體採用優質冷軋鋼板,厚度0.4mm,防銹耐用,不易磨損
- 帶棱柱狀擴散器
- 防塵防蟲



	1235	$\dashv$
		F 60/100 -
( Unit	:: mm )	

17/18

### Specification 產品規格 >>

Model 型號	Size 尺寸	Number Of Tube 燈管數量	Material 材料	IP Grade IP等級	Carton Size 外箱尺寸	PCS / CTN 每箱數量
	(mm)	(pcs)			(mm)	(pcs)
DBA-FA-T0612	1235*60*55	1pcs*1.2m(4ft)	Cold-rolled steel plate	IP 20	1240*200*190	9
DBA-FA-T1012	1235*100*55	2pcs*1.2m(4ft)	Cold-rolled steel plate	IP 20	1240*200*190	6

- The product is a separate bracket, which can be equipped with LED tube as required
- Lamp light effect (lm/W), power (W), color rendering index (CRI), length, can be customized according to customer needs
- 產品為单独支架,可按需求配備LED燈管
- 燈管光效(lm/W)、功率(W)、顯色指數(CRI)、長度,可根據客戶需求定制

Room B3, 18/F Bonsun Industrial Building, 364-366 Sha Tsui Road, Tsuen Wan,HongKong

Phone: 852-39745593

Fax: 852-35440462

info@ilighting.com.hk

NO:5E-6-9-1

NO:5E-6-10-1