

WPD (60W-120W)

壁灯
专业户外照明

WALL LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Large area integrated die-casting aluminum shell, integrated whole lamp heat dissipation

大面积一体压铸铝外壳, 一体化整灯散热

Ultra high temperature lens, baked paint process, corrosion-resistant

多应用, 适合各种复杂多变的应用场合

Elegant and simple appearance, easy installation

外观大方简洁, 安装便捷


Optical PC lens+tempered glass interchangeable, IK08 anti-collision grade, UV resistance, light transmittance up to 90%

光学PC透镜+钢化玻璃互换, IK08防撞等级, 耐紫外线, 透光率达90%

Product specs 产品参数

Model 产品型号	IL-WPD60	IL-WPD80	IL-WPD100	IL-WPD120
Dimension尺寸(mm)	336.3*180.9*217	336.3*180.9*217	299.9*168.8*156.5	299.9*168.8*156.5
Power功率	60W	80W	100W	120W
Voltage输入电压	AC100-277V 50/60Hz			
LED Brand 芯片品牌	Lumileds			
CRI显指	Ra>70/80			
Efficiency光效	110LM/W±10%			
Total Flux(lm)光通量	6600lm	8800lm	11000lm	13200lm
CCT色温	3000K/4000K/5000K/5700K/6500K			
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics			
Beam Angle发光角度	半截光DLC5.2			
IP Grade防护等级	IP66			

Distribution curve flux 配光曲线



Application scenarios 应用场景



WPS (60W-200W)

壁灯
专业户外照明

WALL LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Large area integrated die-casting aluminum shell, integrated whole lamp heat dissipation

大面积一体压铸铝外壳, 一体化整灯散热

Ultra high temperature lens, baked paint process, corrosion-resistant

多应用, 适合各种复杂多变的应用场合

Elegant and simple appearance, easy installation

外观大方简洁, 安装便捷


Optical PC lens, IK08 anti-collision grade, UV resistant, with a transmittance of 90%

光学PC透镜, IK08防撞等级, 耐紫外线, 透光率达90%

Product specs 产品参数

Model 产品型号	IL-WPS60	IL-WPS80	IL-WPS100	IL-WPS120	IL-WPS150	IL-WPS200
Dimension尺寸(mm)	300*169*156.5	300*169*156.5	300*169*156.5	300*169*156.5	365*187*157	365*187*157
Power功率	60W	80W	100W	120W	150W	200W
Voltage输入电压	AC100-277V 50/60Hz					
LED Brand 芯片品牌	Lumileds					
CRI显指	Ra>70/80					
Efficiency光效	110LM/W±10%					
Total Flux(lm)光通量	6600lm	8800lm	11000lm	13200lm	16500lm	22000lm
CCT色温	3000K/4000K/5000K/5700K/6500K					
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics					
Beam Angle发光角度	半截光DLC5.2					
IP Grade防护等级	IP66					

Distribution curve flux 配光曲线



Application scenarios 应用场景

