

TDA (100W-500W)

TOWER PENDANT LIGHT

CE RoHS 5YEAR WARRANTY

塔吊灯
高品质照明



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Fin aluminum+copper tube design, high-quality heat dissipation, anti-corrosion and rust proof, durable and long-lasting

独创的鳍片铝+铜管设计, 高品质导热, 整灯防腐防锈, 持久耐用

Ultra high tempered glass technology, IK08 anti-collision grade, UV resistance, 94% light transmittance

超高钢化玻璃工艺, IK08防撞等级, 抗UV, 透光率94%

Lighting for industrial plants, sports venues, ports, docks, squares, tower cranes, building lighting and other places

工业厂房、体育场馆、港口、码头、广场、塔吊、建筑照明等场所照明

Working environment: -35°C~+50°C

工作环境: -35°C~+50°C

Product specs 产品参数

Model 产品型号	IL-TDA100	IL-TDA150	IL-TDA200	IL-TDA300	IL-TDA400	IL-TDA500
Dimension尺寸(mm)	510*375*285	510*375*285	510*375*285	510*375*285	510*375*285	510*375*285
Power功率	100W	150W	200W	300W	400W	500W
Voltage输入电压	AC100-277V 50/60Hz					
LED Brand 芯片品牌	Lumileds					
CRI显指	Ra>70/80					
Efficiency光效	120LM/W±10%					
Total Flux(lm)光通量	12000lm	18000lm	24000lm	36000lm	48000lm	60000lm
CCT色温	3000K/4000K/5000K/5700K/6500K					
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics					
Beam Angle发光角度	25°/60°/90°					
IP Grade防护等级	IP65					

Optical pattern diagram 光型图



Application scenarios 应用场景



TDH (150W-700W)

TOWER PENDANT LIGHT

CE RoHS 5YEAR WARRANTY

塔吊灯
高品质照明



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Fin aluminum+copper tube design, high-quality heat dissipation, anti-corrosion and rust proof, durable and long-lasting

独创的鳍片铝+铜管设计, 高品质导热, 整灯防腐防锈, 持久耐用

Ultra high tempered glass technology, IK08 anti-collision grade, UV resistance, 94% light transmittance

超高钢化玻璃工艺, IK08防撞等级, 抗UV, 透光率94%

Lighting for industrial plants, sports venues, ports, docks, squares, tower cranes, building lighting and other places

工业厂房、体育场馆、港口、码头、广场、塔吊、建筑照明等场所照明

Working environment: -35°C~+50°C

工作环境: -35°C~+50°C

Product specs 产品参数

Model 产品型号	IL-TDH150	IL-TDH200	IL-TDH300	IL-TDH400	IL-TDH500	IL-TDH600	IL-TDH700
Dimension尺寸(mm)	452*367	450*367	447*367	482*367	512*367	512*367	508*367
Power功率	150W	200W	300W	400W	500W	600	700W
Voltage输入电压	AC100-277V 50/60Hz						
LED Brand 芯片品牌	Lumileds						
CRI显指	Ra>70/80						
Efficiency光效	120LM/W±10%						
Total Flux(lm)光通量	18000lm	24000lm	36000lm	48000lm	60000lm	72000lm	83000lm
CCT色温	3000K/4000K/5000K/5700K/6500K						
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics						
Beam Angle发光角度	25°/60°/90°						
IP Grade防护等级	IP65						

Optical pattern diagram 光型图



Application scenarios 应用场景



TDB (150W-1000W)

塔吊灯
专业工业照明

TOWER PENDANT LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Lightweight finned heat dissipation structure, lightweight, high safety, excellent heat dissipation performance

轻巧鳍片式散热结构, 重量轻, 安全性高, 散热性能优异

Ultra high tempered glass technology, IK08 anti-collision grade, UV resistance, 94% light transmittance

超高钢化玻璃工艺, IK08防撞等级, 抗UV, 透光率94%

Lighting for industrial plants, sports venues, ports, docks, squares, tower cranes, building lighting and other places

工业厂房、体育场馆、港口、码头、广场、塔吊、建筑照明等场所照明

Working environment: -35°C~+50°C

工作环境: -35°C~+50°C

Product specs 产品参数

Model 产品型号	IL-TDB150	IL-TDB200	IL-TDB300	IL-TDB400	IL-TDB500	IL-TDB800	IL-TDB1000
Dimension尺寸(mm)	404*183.5	453.5*183.5	455*183.5	496*208	498*208	570*457	593*510
Power功率	150W	200W	300W	400W	500W	800W	1000W
Voltage输入电压	AC100-277V 50/60Hz						
LED Brand 芯片品牌	Lumileds						
CRI显指	Ra>70/80						
Efficiency光效	130LM/W±10%						
Total Flux(lm)光通量	19500lm	26000lm	39000lm	52000lm	65000lm	104000lm	130000lm
CCT色温	3000K;4000K;5000K;5700K;6500K						
LED Driver 驱动电源	MEAN WELL / MOSO/ Inventronics						
Beam Angle角度	150-300W(25°、60°、90°) / 400-1000W (60°)						
IP Grade防护等级	IP65						

Optical pattern diagram 光型图



Application scenarios 应用场景



TDC (200W-1000W)

塔吊灯
专业工业照明

TOWER PENDANT LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Lightweight finned heat dissipation structure, lightweight, high safety, excellent heat dissipation performance

轻巧鳍片式散热结构, 重量轻, 安全性高, 散热性能优异

Ultra high tempered glass technology, IK08 anti-collision grade, UV resistance, 94% light transmittance

超高钢化玻璃工艺, IK08防撞等级, 抗UV, 透光率94%

Lighting for industrial plants, sports venues, ports, docks, squares, tower cranes, building lighting and other places

工业厂房、体育场馆、港口、码头、广场、塔吊、建筑照明等场所照明


Working environment: -35°C~+50°C

工作环境: -35°C~+50°C

Product specs 产品参数

Model 产品型号	IL-TDC200	IL-TDC300	IL-TDC400	IL-TDC500	IL-TDC800	IL-TDC1000
Dimension尺寸(mm)	379*367	488*426	573*449	573*449	500*425	658*599
Power功率	200W	300W	400W	500W	800W	1000W
Voltage输入电压	AC100-277V 50/60Hz					
LED Brand 芯片品牌	Lumileds					
CRI显指	Ra>70/80					
Efficiency光效	130LM/W±10%					
Total Flux(lm)光通量	26000lm	39000lm	52000lm	65000lm	104000lm	130000lm
CCT色温	3000K/4000K/5000K/5700K/6500K					
LED Driver 驱动电源	MEAN WELL / MOSO/ Inventronics					
Beam Angle发光角度	200W(25°、60°、90°) / 300-1000W (60°)					
IP Grade防护等级	IP65					

Optical pattern diagram 光型图



Application scenarios 应用场景

