

# GSH (100W-240W)

加油站灯  
专业工业照明

## GAS STATION LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Die cast aluminum alloy shell with strong air convection design to enhance heat dissipation efficiency

压铸铝合金外壳, 空气强对流设计, 提升散热效能

Thick tempered glass face mask, resistant to pressure, cracking, high temperature, and good transparency

加厚钢化玻璃面罩, 抗压防裂耐高温, 透光性好

Powder coating process on the surface of the lamp body, regular white, accepting special color customization

灯体表面喷粉工艺, 常规白色, 接受特殊颜色定制

Indoor and outdoor lighting for gas stations, ceilings, factories, workshops, ceilings, warehouses, etc

加油站、天棚、工厂、车间、天花、仓库等室内外照明

### Product specs 产品参数

Model 产品型号	IL-GSH100	IL-GSH150	IL-GSH200	IL-GSH240
Dimension尺寸(mm)	420*420*67	420*420*67	540*540*67	540*540*67
Power功率	100W	150W	200W	240W
Voltage输入电压	AC100-277V 50/60Hz			
LED Brand 芯片品牌	Lumileds /CREE			
CRI显指	Ra>70/80			
Efficiency光效	130LM/W±10%			
Total Flux(lm)光通量	13000lm	19500lm	26000lm	31200lm
CCT色温	3000K/4000K/5000K/5700K/6500K			
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics			
Beam Angle发光角度	120°			
IP Grade防护等级	IP65			

### Optical pattern diagram 光型图



120°



### Application scenarios 应用场景



# GSA (40W-80W)

加油站灯  
专业工业照明

## GAS STATION LIGHT

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

ADC12 die cast aluminum, integrated molding process, large heat dissipation area, good thermal conductivity

ADC12压铸铝, 一体成型工艺, 散热面积大, 导热性好

Adopting PC lampshade, IK08 anti-collision rating, UV resistance, and a light transmittance of 94%

采用PC灯罩, IK08防撞等级, 抗UV, 透光率94%

Powder coating process on the surface of the lamp body, conventional brown gray color, supports color customization

灯体表面喷粉工艺, 常规棕灰色, 支持颜色定制

Indoor and outdoor lighting for gas stations, ceilings, factories, workshops, ceilings, warehouses, etc

加油站、天棚、工厂、车间、天花、仓库等室内外照明


### Product specs 产品参数

Model 产品型号	IL-GSA40	IL-GSA60	IL-GSA80
Dimension尺寸(mm)	243*243*85	243*243*85	243*243*85
Power功率	40W	60W	80W
Voltage输入电压	AC100-277V 50/60Hz		
LED Brand 芯片品牌	Lumileds		
CRI显指	Ra>70/80		
Efficiency光效	120LM/W±10%		
Total Flux(lm)光通量	4800lm	7200lm	9600lm
CCT色温	3000K/4000K/5000K/5700K/6500K		
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics		
Beam Angle发光角度	120°		
IP Grade防护等级	IP65		

### Optical pattern diagram 光型图



120°



### Application scenarios 应用场景

