

**GLM** (80W-150W)

庭院灯  
专业户外照明

GARDEN LAMP

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Large area integrated die-casting aluminum shell, integrated whole lamp heat dissipation

大面积一体压铸铝外壳, 一体化整灯散热

Ultra high temperature lens, baked paint process, corrosion-resistant

多应用, 适合各种复杂多变的应用场合

Elegant and simple appearance, easy installation

外观大方简洁, 安装便捷

Optical PC lens+tempered glass interchangeable, IK08 anti-collision grade, UV resistance, light transmittance up to 90%

光学PC透镜+钢化玻璃互换, IK08防碰撞等级, 耐紫外线, 透光率达90%

### Product specs 产品参数

Model 产品型号	IL-GLM80	IL-GLM100	IL-GLM120	IL-GLM150
Dimension尺寸(mm)	Φ360*H504	Φ360*H504	Φ360*H504	Φ360*H504
Power功率	80W	100W	120W	150W
Voltage输入电压	AC100-277V 50/60Hz			
LED Brand 芯片品牌	Lumileds			
CRI显指	Ra>70/80			
Efficiency光效	120LM/W±10%			
Total Flux(lm)光通量	9600lm	12000lm	14400lm	18000lm
CCT色温	3000K/4000K/5000K/5700K/6500K			
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics			
Beam Angle发光角度	120°			
IP Grade防护等级	IP66			

### Distribution curve flux 配光曲线



120°



### Application scenarios 应用场景



**GLS** (50W-200W)

庭院灯  
专业户外照明

GARDEN LAMP

CE RoHS 5YEAR WARRANTY



Imported Lumileds light source, high brightness, low light decay, long lifespan

进口Lumileds光源, 高亮度、低光衰、寿命长

Large area integrated die-casting aluminum shell, integrated whole lamp heat dissipation

大面积一体压铸铝外壳, 一体化整灯散热

Ultra high temperature lens, baked paint process, corrosion-resistant

多应用, 适合各种复杂多变的应用场合

Elegant and simple appearance, easy installation

外观大方简洁, 安装便捷

Optical PC lens, IK08 anti-collision grade, UV resistant, with a transmittance of 90%

光学PC透镜, IK08防碰撞等级, 耐紫外线, 透光率达90%


### Product specs 产品参数

Model 产品型号	IL-GLS50	IL-GLS60	IL-GLS80	IL-GLS100	IL-GLS120	IL-GLS150
Dimension尺寸(mm)	400*508	400*508	400*508	400*508	446*508	446*508
Power功率	50W	60W	80W	100W	120W	150W
Voltage输入电压	AC100-277V 50/60Hz					
LED Brand 芯片品牌	Lumileds					
CRI显指	Ra>70/80					
Efficiency光效	120LM/W±10%					
Total Flux(lm)光通量	6000lm	7200lm	9600lm	12000lm	14400lm	18000lm
CCT色温	3000K/4000K/5000K/5700K/6500K					
LED Driver 驱动电源	MEAN WELL / MOSO / Inventronics					
Beam Angle发光角度	120°					
IP Grade防护等级	IP66					

### Distribution curve flux 配光曲线



120°



### Application scenarios 应用场景

