

Wide angle LED T8 Tube



**Model : LT-I0609/LT-I1218/LT-I1522
(-S series)**

Features:

1. Uniform light emission
2. High luminous output 150lm/W & Low power consumption
3. SPM Design – power circuit protection to cut off individual LEDs when mal-functioned



Model:LT-I0609
LT-I1218
LT-I1522
(-S series)

Standard

Tube Dimension	Ø 26.5mm*588mm/1198mm/1498mm
Voltage (V)	AC85~265V
Lamp Holder	T8, G13
Beam Angle	300 degree
CRI	>80Ra
Luminous Efficacy	150 lm/W
Power Factor	> 0.90
Power Efficiency	90%
Gear loss	10%

Model:	Output power	8.1W
LT-I0609	Gear loss	0.9W
	Input power	9W

Model:	Output power	16.2W
LT-I1218	Gear loss	1.8W
	Input power	18W

Model:	Output power	19.8W
LT-I1522	Gear loss	2.2W
	Input power	22W

Model:	9W / 150lm/W / Total 1350lm
LT-I0609	

Model:	18W / 150lm/W / Total 2700lm
LT-I1218	

Model:	22W / 150lm/W / Total 3300lm
LT-I1522	

Cover Material	Aluminium , PC Cover
Color Temperature	2700K /3000K / 4000K / 6000K
Life Time	50,000(H)

EMC	EN55015:2006; EN61547:2009; EN61000-3-2:2006+A1:2009+A2:2009; EN61000-3-3:2008 IEC60598-2-1:1989&EN60598-1:2008 EN60598-1:2015
LVD	IEC62560-2011 IEC62031:2008 IEC61347-2-13:2006 IEC61347-1:2007+A1:2010 EN62776

